



SeaEco

Reference# 82603-55290STD

SeaEco

SeaEco is one of our best-selling standard immersion suits. The suit is manufactured in 5mm flame-retardant neoprene and our focus has been on quality and safety. SeaEco is a 6-hour immersion suit that must be used with certified lifejacket. SeaEco can be supplied individually vacuum packed and takes up little space. It is ideal for vessels destined for cold water regions and that already have certified lifejackets on board.

Facts

- Immersion suit for the merchant vessels etc
- Flame retardant 5mm neoprene with knitted polyester backing for durability
- Waterproof main zipper in soft PU/Plastic - easy to close
- Approved reflective patches
- Integrated neoprene hood
- Watertight cuffs
- Detachable gloves attached by elastic bands - stored under flap on sleeves
- Rubber soles for optimal grip on slippery surface
- 6 hours thermal protection in cold water $<2^{\circ}\text{C}$ watertemperature
- SOLAS approved and in accordance with the LSA code MED 1.5b as an insulated immersion suit, designed to be worn with a life-jacket
- May be vacuum packed for extended service intervals (maximum 10 years)
- When stored without vacuum it is required with regular control and lubrication of the main zipper. Zip should be in closed position when stored.
- When used with SeaLion 275N IMO/SOLAS life-jacket and Seacrewssader/Ergofit 275N: Mensafe HSE UK Compatible

Product Detail

Area of application	<i>Shipping</i>
Type of suit	<i>Evacuation/emergency suit Survival/immersion suit</i>
Material	<i>Neoprene 5mm w/single knitted polyester backing</i>
Adjustments	<i>Adjustment strap on lower leg/ankle w/velcro</i>
Main zipper type	<i>Polyurethane/plastic spiral, open</i>
Wrist seals	<i>Neoprene with velcro adjustment</i>
Colour	<i>Orange</i>
Reflective material	<i>IMO Solas</i>
Hood	<i>Integral, in suit material</i>
Gloves	<i>3-finger neoprene (detachable)</i>
Boots / socks	<i>Neoprene socks with FR heavy duty rubber sole</i>
Compatibility	<i>Yes, IMO with IMO lifejacket</i>
Thermal protection with lining/inherent insulation	<i>6 hours (IMO/Solas less than 2°C watertemp)</i>
Service interval (standard)	<i>3 year</i>
Service Interval (in HP-vacuum)	<i>10 years - manufacturer's recommendation</i>
Service interval (HP-vacuum)	<i>Note: Some flag states may have specific regulations with regards to service</i>
Other certifications	<i>Mensafe HSE UK Compatibility</i>
Certifications SOLAS-suit (w/o integral buoyancy)	<i>Solas MED/1.5b (with inherent insulation)</i>

Certificates

SOLAS

RMRS

Red Ensign

MENSAFE
SeaLion

MENSA
crewsa
of

Contact us

Hansen Protection AS, PB. 218, N-1501 Moss

Tel. +47 69 00 13 00, e-post: hpro@hansenprotection.no