



SeaLion Fluorescent Yellow ISO 150N

Reference# 83119-05300 STD

SeaLion Fluorescent Yellow ISO 150N

SeaLion lifejackets are designed for users with high demands on function and comfort. This lifejacket can be used in combination with our work/immersion suits and provide 150N buoyancy. SeaLion 150N lifejacket is designed to inflate automatically in contact with water and contribute to the turning of the body face up also when wearing a suit. The hydrostatic inflator mechanism will make sure that the lung will not inflate unintended. Certified in accordance with ISO 12402-3

Facts

- Lightweight and comfortable, construction with focus on comfort
- Contoured around head and neck + soft neoprene in neck
- Rough, durable cover fabric in fluorescent yellow
- Easy operated front buckle in plastic
- Adjustment of waist webbing in the side
- UML inflators - water activated (automatic)
- Retro reflective tape (SOLAS)
- Whistle, lifting loop and emergency light
- Double crotch strap
- Double buoyancy bladder in high-vis material
- Service friendly - buoyancy bladder may easily be detached from cover

Product Detail

Lifejacket	<i>Lifejacket work</i>
Type of PFD/class	<i>Inflatable lifejacket 150N</i>
Area of application	<i>Shipping</i>
Buoyancy	<i>Minimum 150N</i>
Material	<i>Polyester</i>
Adjustments	<i>Crotch Strap Waist</i>
Fit / Ergonomics	<i>Ergonomic Long</i>
Colour	<i>300 Fluor Yellow</i>
Reflective material	<i>IMO Solas</i>
Bladder construction	<i>Symmetrical</i>
Firing mechanism	<i>Water activated, UML Auto MK 5</i>
Whistle	<i>Yes</i>
Emergency light	<i>IMO Solas, water activated</i>
Inspection window for inflator	<i>Yes</i>
Buckle	<i>Plastic buckle with quick release functionality</i>
Cover closure	<i>Velcro</i>
Compatibility	<i>Yes, ISO with ISO suit</i>
CO₂-cylinder(s)	<i>33g CO₂ (1pc)</i>
Service interval (standard)	<i>1 year (professional use) 2 year (leisure)</i>
Certifications ISO	<i>ISO 12402-3 Lifejackets for offshore conditions (150N)</i>
Crotch strap	<i>Single</i>

Certificates

ISO 12402-3

Contact us

Hansen Protection AS, PB. 218, N-1501 Moss
Tel. +47 69 00 13 00, e-post: hpro@hansenprotection.no