



SeaEco+ with rescue harness

Reference# 82610-55290STD

SeaEco+ with rescue harness

SOLAS and CE approved immersion suit with integrated rescue harness for quick and safe evacuation. The safe choice for evacuation from offshore wind turbines. Built-in buoyancy in the collar ensures proper a floating position and adequate freeboard. Vacuum packing saves space and extends the mandatory service interval, which in turn makes this suit excellent value.

Facts

- Buoyancy pillow in back ensures correct floating position and free-board
- Flame retardant 5 mm neoprene with knitted polyester backing for durability
- · With buddy line and floating hook
- Inetgrated rescue harness approved iaw EN 1498
- Lifting strap with stainless steel D-ring and carbine hook
- Waterproof main zip in PU/Plastic easy to close
- Approved reflective patches
- · Integrated hood with extra closure
- · Watertight cuffs
- Detachable gloves attached by elastic bands stored under flap on sleeves
- Velcro tighteners in legs
- Rubber soles for optimal grip on slippery surface
- SOLAS improved and in accordance with LSA code MED 1.6b as an insulated immersion suit designed to be worn without a life-jacket
- Option for emergency light with extended expiry (15 years)
- With optional long-life emergency light the suit can be vacuum packed for 15 years service interval (Remark: With special DDP)
- May be vacuum packed for extended service interval
- When stored without vacuum it is required with regular control and lubrication of the main zipper. Zip should be in closed position when stored.

Product Detail	
Area of application	Offshore Wind Energy
Type of suit	Evacuation/emergency suit Survival/immersion suit
Material	Neoprene 5mm w/single knitted polyester backing
Adjustments	Adjustment strap on lower leg/ankle w/velcro
Main zipper type	Polyurethane/plastic spiral, open
Wrist seals	Neoprene with velcro adjustment
Colour	Orange
Reflective material	IMO Solas
Hood	Integral, in suit material
Gloves	3-finger neoprene (detachable)
Lifting becket/loop	Yes, with D-ring and carbine hook in stainless steel
Buddy line	Yes, with floating carbine hook
Whistle	Yes, easy accessible in zipper slider
Emergency light	IMO Solas, water activated
Boots / socks	Neoprene socks with FR heavy duty rubber sole
Compatibility	May be used without lifejacket
Thermal protection with lining/inherent insulation	6 hours (IMO/Solas less than 2°C watertemp)
Service interval (standard)	3 year
Service Interval (in HP-vacuum)	5 years - manufacturer's recommendation 15 years - provided acceptance of non-approved emergency light
Service interval (HP-vacuum)	Note: Some flag states may have specific regulations with regards to service
Certifications SOLAS-suit (w/integral buoyancy)	Solas MED/1.6b (with inherent insulation - to be worn without lifejacket)
Certifications ISO	ISO 15027-2 Abandonment suits
Integral Rescue Harness	Yes, with D-ring i stainless steel approved iaw EN 1498:2006

Certificates

Contact us

SOLAS

ISO 15027-2:2012



Tel. +47 69 00 13 00, e-post: hpro@hansenprotection.no

hansenprotection.no