



## **Crewfit 180N Pro Automatic**

Reference# 83400-9020BRA

## **Crewfit 180N Pro**

An everyday boating lifejacket designed using 3D technology to radically increase comfort levels. Successful integration of a high volume 3D shaped bladder design, a peninsula chin support and increased buoyancy to 180N provides you with maximum in water performance.

The Crewfit 180N Pro wraps all of these safety features into a fun, stylish, 3D shaped and super comfy cover.

### **Facts**

- The fusion 3D construction ensures an ergonomic shape for comfort and freedom of movement
- Indicator window showing the status of the inflator
- EXOLOK provides a clear indication if the cylinder moves, becomes unscrewed or is tampered with
- Designed with a Peninsular Chin support, to keep your airway well clear of the water whatever the conditions
- Attachment point for S20 AIS unit
- Built in Crewsaver Surface Light (CSL) to help attract attention when inflated, light activated automatically on contact with water and can be activated manually if needed
- Soft loop D-ring for attaching safety harness (with harness option)
- With crotch strap and lifting becket
- Quick Burst Zipper for safe inflation
- Robust outer cover for durability
- Twin, forward pull side waist adjusters
- ISO 12402-3 (150N) approved but with superior buoyancy (180N) for a higher floating position in the water

## Product Detail

<b>Lifejacket</b>	<i>Lifejacket work</i>
<b>Type of PFD/class</b>	<i>Inflatable lifejacket 150N</i>
<b>Area of application</b>	<i>Shipping</i>
<b>Buoyancy</b>	<i>Minimum 150N</i>
<b>Adjustments</b>	<i>Crotch Strap Waist - both sides</i>
<b>Fit / Ergonomics</b>	<i>Fusion 3D Design</i>
<b>Colour</b>	<i>Black</i>
<b>Reflective material</b>	<i>IMO Solas</i>
<b>Bladder construction</b>	<i>Symmetrical with chin support</i>
<b>Firing mechanism</b>	<i>Water activated, UML ProSensor Elite</i>
<b>Lifting becket/loop</b>	<i>Yes</i>
<b>Whistle</b>	<i>Yes</i>
<b>Emergency light</b>	<i>IMO Solas, water activated</i>
<b>Inspection facility for inflation mechanism</b>	<i>Yes, inspection window in transparent foil</i>
<b>Deck Safety Harness</b>	<i>Yes, with soft loop D-ring (for variant with safety harness)</i>
<b>Buckle</b>	<i>Stainless Steel (for variant with safety harness)</i>
<b>Cover closure</b>	<i>Zipper with Quick Burst functionality</i>
<b>Compatibility</b>	<i>Yes, ISO with ISO suit</i>
<b>CO<sub>2</sub>-cylinder(s)</b>	<i>38g CO<sub>2</sub> (1 pc)</i>
<b>Service interval (standard)</b>	<i>1 year (professional use) 2 year (leisure)</i>
<b>Certifications ISO</b>	<i>ISO 12402-3 Lifejackets for offshore conditions (150N)</i>
<b>Weight</b>	<i>1,0 kg with plastspenne/1,1 kg with sikkerhetssele</i>
<b>Crotch strap</b>	<i>Double detachable</i>
<b>Cylinder security system</b>	<i>Yes, EXOLOK</i>
<b>Waist belt min-max length</b>	<i>Min 75 cm - max 155 cm</i>

## Certificates

ISO 150N Certificate

ISO 150 Type Exam  
Report

DOC

Contact us

Hansen Protection AS, PB. 218, N-1501 Moss

Tel. +47 69 00 13 00, e-post: [hpro@hansenprotection.no](mailto:hpro@hansenprotection.no)