



## **Crewline Pro Safety Lines**

Reference# 83286

## **Crewline Pro Safety Lines**

The Crewline Pro safety line range is designed to prevent the user from falling overboard from the vessel in rough conditions. Constructed using self-locking safety hooks, with a wide opening, allows the user to easily attach the Crewline Pro to the attachment point on a lifejacket or safety harness and a suitable anchor point on the vessel/yacht as required.

Constructed from a durable, hydrophobic webbing helps to keep the safety line as light as possible, even in the harshest environments, as it reduces the amount of water absorbed compared with conventional safety lines. This combined with its advanced hook makes the Crewline Pro a first choice for those exposed for the ultimate challenging environments where nothing but the very best in performance technology will do.

Each Crewline Pro includes an overload indicator which is activated when the line is placed under an excessive load of 400 kg. There is additionally a warning label which, when exposed, means the safety line should not be used. The range is available in four variants – including elastic and non-elastic with a choice of a single, double or triple hook set up.

### **Facts**

- Lightweight self-locking hook
- Reflective detailing
- Compact
- Constructed from a durable, hydrophobic webbing
- Electric neon colourway
- Easy to use
- Overload indicator (maximum weight 400 kg)

## Product Detail

<b>Area of application</b>	<i>Multi-purpose</i>
<b>Colour</b>	<i>Black/neon with reflective detailing</i>
<b>Safety features</b>	<i>Overload indicator</i>
<b>Hook</b>	<i>Self-locking in lightweight aluminium</i>
<b>Webbing</b>	<i>Hydrophobic and durable</i>

## Certificates

ISO 12401

EC Declaration

*Contact us*

Hansen Protection AS, PB. 218, N-1501 Moss  
Tel. +47 69 00 13 00, e-post: [hpro@hansenprotection.no](mailto:hpro@hansenprotection.no)