



## SeaLion Europe Passenger 275N for CA EBS

Reference# 82998

## SeaLion Europe 275N Passenger with CA EBS

An advanced, well-equipped lifejacket for passengers in helicopters operating over open waters. This lifejacket is intended and certified for use with our SeaAir EBS compressed air emergency breathing system (EBS) that is purchased separately. The EBS is designed to make it possible to start breathing under water if the helicopter ditches. The lifejacket's minimum 275N buoyancy is activated manually for safe evacuation of a ditched helicopter.

### Facts

- Actual buoyancy is 300N
- Manually activated 60g CO<sub>2</sub> cylinder
- Prepared for integration of SeaAir CA EBS (Compressed Air EBS)
- Sprayhood, crotch strap, emergency light and whistle
- Stainless steel buckle safe attachment and quick adjustment to various body sizes
- Designed for adults (one size fits all)
- Please note: SeaAir CA EBS delivered separately
- Compatible with SeaAir integrated suits, SeaAir Europe Passenger and Pilot suits and SeaWind triple approved suit
- Approved in accordance with EASA ETSO 2C504 and for integration with SeaAir EBS according to CAA-UK CAP 1034

## Product Detail

<b>Redningsvest</b>	<i>Helikopter</i>
<b>Bruksområde</b>	<i>Helikopter passasjer</i>
<b>Oppdrift</b>	<i>Minimum 275N</i>
<b>Materiale</b>	<i>Polyester</i>
<b>Justeringer</b>	<i>Midje</i>
<b>Fit / Ergonomics</b>	<i>Long</i>
<b>Colour</b>	<i>Black</i>
<b>Reflective material</b>	<i>IMO Solas</i>
<b>Pockets</b>	<i>Integrated pocket for Cat A EBS according to CAP 1034</i>
<b>Bladder construction</b>	<i>Symmetrical</i>
<b>Operating head</b>	<i>Manual, UML MK 2 Mini Manual, UML Micro</i>
<b>Sprayhood</b>	<i>Yes</i>
<b>PLB</b>	<i>None</i>
<b>Buddy line</b>	<i>Yes</i>
<b>Whistle</b>	<i>Yes</i>
<b>Deck Safety Harness</b>	<i>No</i>
<b>Buckle</b>	<i>Stainless steel with quick release functionality</i>
<b>Cover closure</b>	<i>Zipper with Quick Burst functionality</i>
<b>Compatibility</b>	<i>Yes, ETSO with ETSO suit</i>
<b>CO<sub>2</sub>-cylinder(s)</b>	<i>60g CO<sub>2</sub> (1 pc)</i>
<b>Service interval (standard)</b>	<i>1 year</i>
<b>Certifications ETSO</b>	<i>ETSO 2C504 (Helicopter lifejacket)</i>
<b>Crotch strap</b>	<i>Double</i>

## Certificates

ETSO

Contact us

Hansen Protection AS, PB. 218, N-1501 Moss  
Tel. +47 69 00 13 00, e-post: [hpro@hansenprotection.no](mailto:hpro@hansenprotection.no)